



MÄK Data Logger 3.11.5 Release Notes

This document provides the following release-specific information for MÄK Data Logger 3.11.5:

Systems Supported	2
Logger API and Logger File API	2
Qt Toolkit Compatibility	2
RAM and Memory Requirements	2
Compiler Compatibility on Windows	2
Network Compatibility	3
RTI Support	3
FOM Support	3
Fixed Bugs	4
Known Problems	4

Copyright © 2006 MÄK Technologies, 68 Moulton St., Cambridge, MA 02138 All rights reserved.
MÄK Technologies®, VR-Forces®, RTIspey®, and VR-Link® are registered trademarks of
MÄK Technologies, Inc.
Document ID: LOG-3.11.5-2-060124

Systems Supported

Logger 3.11.5 is being released for the following platforms:

- Ê PC with Windows 2000/XP, Visual C++ 7.1
- Ê Red Hat Linux 9.0, Workstation Enterprise 3, Fedora Core 3
- Ê SGI IRIX 6.5 n32
- Ê Sun Solaris version 2.8.

Logger API and Logger File API

You must have VR-Link 3.9.3 and its required compiler versions to use the Logger file library or the Logger API, but you do not need it to run the executables. See VR-Link documentation for information about required compiler versions.

You must have a VR-Link developer's license to compile plug-ins or applications that use the Logger API or Logger file API.

Qt Toolkit Compatibility

The Logger GUI is built using the Qt Toolkit, a cross-platform GUI toolkit. If you use the Logger API to change the GUI, you need to get a Qt license and install Qt. Logger 3.11.5 was built with Qt 3.3.1.

RAM and Memory Requirements

To install and run the Logger on a PC, we recommend the following minimum configuration:

- Ê Pentium class PC 400 MHz or above
- Ê 150 MB disk space
- Ê 64 MB RAM.

On UNIX systems, the Logger requires the following amount of disk space:

- Ê Linux - 150 MB
- Ê Sun Solaris - 185 MB
- Ê SGI IRIX - 325 MB.

Compiler Compatibility on Windows

MÄK provides versions of product releases that have been compiled with Microsoft Visual C++ 6.0 and 7.1. When you run MÄK products together, for example, the Logger and the Stealth, we strongly recommend that you run versions compiled with the same compiler. Mixing products compiled with different versions of the compiler can result in program instability.

Network Compatibility

HLA only

Logger 3.11.5 was built against VR-Link 3.9.3 and is compliant with:

- Ê RPR-FOM 1.0 and a subset of 2.0 (draft 6, 14, and 17)
- Ê MÄK RTI 2.4.

DIS only

Logger 3.11.5 supports DIS 2.0.4, IEEE 1278.1, 2.1.4, and IEEE 1278.1a, and can therefore interoperate with DIS applications of any of these versions.

RTI Support

Logger 3.11.5 works with the MÄK RTI 2.x, and DMSO RTI NG v6.

Logger 3.11.5 works with older versions of the MÄK RTI, but we recommend using it with release 2.4.

When using the MÄK Real-time RTI, remember to make sure that the Logger can find your FED file, and optional *rid.mtl*, file by either putting them in the directory from which you are running, or by setting the environment variable RTI_CONFIG to the directory that contains them.

FOM Support

Logger 3.11.5 has built-in support for versions 0.5, 0.7, 0.8, 1.0, and 2.0, drafts 6, 14, and 17, of the RPR FOM. It also supports VR-Link's ability to support alternative FOMs through the FOM Mapper. By default, Logger 3.11.5 uses RPR FOM 1.0.

The keywords for specifying different versions of the RPR FOM with the `-f` startup option are:

- Ê RPR FOM 0.5: `v1RPR05`
- Ê RPR FOM 0.7: `v1RPR07`
- Ê RPR FOM 0.8: `v1RPR08`
- Ê RPR FOM 1.0: `v1RPR10`
- Ê RPR FOM 2.0 draft 6: `v1RPR20006`
- Ê RPR FOM 2.0 draft 14: `v1RPR20014`
- Ê RPR FOM 2.0 draft 17: `v1RPR20017`.

For information about FOM mapping and selecting the correct FOM mapper, see Configuring the Logger for HLA in Chapter 2, "Installing and Configuring the Logger", in *MÄK Data Logger User's Guide*.

Fixed Bugs

This release fixes a problem with the first timestamp in the empty checkpoint at the start of a Logger file.

Known Problems

Logger 3.11.5 has the following known problems:

- The lgrTrim utility does not work with HLA recordings.