



MAK Data Logger 5.5.1 Release Notes

This document provides the following release-specific information:

Systems Supported.....	2
Logger API.....	2
Qt Toolkit Compatibility.....	2
Starting MAK Applications on Windows 10.....	3
Compiler Compatibility on Windows	3
License Manager	3
ODBC Driver Support	4
Network Compatibility.....	4
RTI Support	4
FOM Support	4
Backwards Compatibility.....	5
New Features.....	5
Documentation Updates.....	5
Bug Fixes	5
Known Problems.....	5
Playing HLA 1.3 Logger Files in HLA 1516 Federations	6

Copyright © 2018 VT MAK, 150 Cambridge Park Drive, Third Floor, Cambridge, MA 02140 All rights reserved. VR-Exchange™, VR-TheWorld™, VR-Vantage™, DI-Guy™, and DI-Guy Scenario™ are trademarks of VT MAK. MAK Technologies®, VR-Forces®, RTIspey®, B-HAVE®, and VR-Link® are registered trademarks of VT MAK.
Document ID: LOG-5.5.1-2-180406

Systems Supported

Table 1-1 lists the platforms currently supported by MAK Logger 5.5.1. Application code must be built with the indicated compilers in order to link to Logger libraries.

Table 1-1: Platforms supported

Platform	Compiler
Red Hat Enterprise Linux Workstation 6.0	Default compiler (64-bit)
Red Hat Enterprise Linux Workstation 7.0	Default compiler (64-bit)
PC with Windows 7, Windows 8, Windows 10	Microsoft Visual C++ 10.0 (64 bit)
	Microsoft Visual C++ 12.0 (64 bit)
	Microsoft Visual C++ 14.0 (64 bit)

Logger API

You must have VR-Link 5.4 and its required compiler versions to link the Logger libraries, but you do not need it to run the executables. Please see VR-Link documentation for information about required compilers.

You must have a VR-Link developer's license to compile plug-in or applications using the Logger API.

Qt Toolkit Compatibility

The Logger GUI is built using the Qt Toolkit, a cross-platform GUI toolkit. Logger 5.5.1 uses Qt 5.5.1. You do not need Qt to do development that does not affect the GUI.

If you plan to build the Logger GUI, you must download and install the appropriate version of Qt. You can download it at:
<http://www.mak.com/support/bonus-material>.

Qt is also available as a free download under the LGPL version 2.1 license at qt.digia.com. This version should be satisfactory for most Logger customers. If you need a Qt commercial license, you must purchase the license from Digia.

Starting MAK Applications on Windows 10

The Windows 10 “All apps” menu does not support the folder structure that MAK uses to organize startup shortcuts for applications, documentation, and tools. Everything gets dumped into a flat list under **MAK Technologies**. This makes finding the application you want to run tedious at best and confusing at worst, particularly if you have multiple versions of an application installed.

Fortunately, there is a fairly simple way to work around this problem. You can create a toolbar that points to the MAK Technologies shortcuts folder. To do this:

1. Right-click the Taskbar at the bottom of the screen.
2. On the pop-up menu, choose **Toolbars** → **New Toolbar**. The New Toolbar - Choose a folder window opens.
3. In the Folder window, type: C:\ProgramData\Microsoft\Windows\Start Menu\Programs\MAK Technologies
4. Click Select Folder.

A new toolbar is added to the Taskbar. To open a MAK application, users guide, or tool, select it from the toolbar.

Compiler Compatibility on Windows

Current and prior releases of MAK products have been compiled using different versions of the Visual C++ compiler. When you run MAK products together, for example, the Logger and VR-Vantage, we strongly recommend that you run versions created with the same compiler. Mixing products compiled with different compilers can result in program instability.

License Manager

To run the licensed version of Logger, you must install license management software. Logger 5.5.1 uses FLEXlm 11.13.0.2. If you are upgrading from a version of the MAK Data Logger that used an older version of FLEXlm, you must upgrade your license management files. You do not need a new license. Licenses are forward compatible.

The License Manager files are not part of the Logger installer. You can download them at:

- ♦ Windows: <ftp://ftp.mak.com/out/MAKLicenseManager-win64-setup.exe>
- ♦ Linux: <ftp://ftp.mak.com/out/MAKLicenseManager-linux64-setup.tar.gz>

A license manager support is available at:

<http://www.mak.com/support/licenses>

ODBC Driver Support

The Logger database export feature supports the following ODBC drivers:

- ♦ MySQL ODBC 2.50 Driver
- ♦ MySQL ODBC 5.351 Driver
- ♦ MySQL ODBC 5.1 Driver
- ♦ MySQL ODBC 5.2w Driver.
- ♦ Microsoft Access.

A 64 bit connector is required.

The MySQL 5.1 server and connector can be downloaded at:

- ♦ server: <http://dev.mysql.com/downloads/mirror.php?id=411970>
- ♦ connector: <http://dev.mysql.com/downloads/mirror.php?id=411736>

Network Compatibility

HLA only

Logger 5.5.1 was built against VR-Link 5.4 and is compliant with:

- ♦ RPR-FOM 1.0, RPR FOM 2.0 drafts 6, 14, 17, and 20, and RPR FOM 2.0 (final version).
- ♦ MAK RTI 4.1 or later.

DIS only

Logger 5.5.1 supports DIS 4, 5, 6, and 7.

RTI Support

We recommend using the latest version of the MAK RTI. However, the Logger should work with other RTIs that conform to the HLA 1.3 specification, the IEEE 1516 SISO DLC API, or HLA Evolved and are built using the same compiler as your version of the Logger.

When using the MAK RTI, remember to make sure that the Logger can find your FED file, and optional *rid.mtl*, file by either putting them in the directory from which you are running, or by setting the environment variable the directory that contains them.

FOM Support

Logger 5.5.1 has built-in support for RPR FOM versions 0.5, 0.7, 0.8, 1.0, 2.0 drafts 6, 14, 17, and 20, and RPR FOM 2.0 final version. It also supports VR-Link's ability to support alternative FOMs through the FOM Mapper. By default, Logger 5.5.1 uses RPR FOM 2.0.

For information about FOM mapping and selecting the correct FOM Configuring the Logger for HLA in Chapter 2, "Installing and Configuring the Logger", in *MAK Data Logger Users Guide*.

Backwards Compatibility

The Logger file format has changed. Logger 5.4 can play files recorded with previous versions. It may prompt you to save them to the current format. Files recorded by Logger 5.4 cannot be played by previous versions of the Logger.

New Features

Logger 5.5.1 has the following new features.

- ♦ Support for a C# remote control API.
- ♦ The location and size of the Logger window is automatically saved when you exit. You can specify the location of the GUI configuration file in a Logger configuration file (for example *lgrConfigDIS.xml*) and on the command line (with the `SetGuiConfigFilename` command).

Documentation Updates

All documentation has been updated for this release.

Bug Fixes

This release fixes the following problems:

- ♦ When using the remote control GUI, playing to the end of the tape will no longer put the remote control into a bad state where logger is stopped but remote control is still in "playing" state. 61514
- ♦ Logger no longer crashes when processing a packet that contains a bad PDU (for example, DIS version == 0). 61681

Known Problems

This section lists known problems with Logger functionality:

- ♦ The HLA 1516 Logger crashes on exit if you use the MAK RTI 2.4.2 through 3.1.1. This is due to a problem in the RTI.
- ♦ Logger files that include the VR-Forces embarkation feature in DIS exercises do not reset embarkation status after time jumps. To correct the embarkation state of entities, stop playback and start playing the file from the beginning.
- ♦ On Linux, online help may not work if the Logger lib directory is not in the LD-LIBRARY_PATH or the RTI *lib* directory is before it.

Playing HLA 1.3 Logger Files in HLA 1516 Federations

In general, the Logger uses the same file format for HLA 1.3 and HLA 1516 Logger files. You can record a Logger file from an HLA 1.3 federation, and play it back into an HLA 1516 federation (and vice versa). However, you must use the same FOM representation during record and playback. For example, if you use an HLA-1.3-style FED file during recording, you must use an HLA-1.3 style FED file during playback, even if you are using the IEEE 1516 version of the Logger and an IEEE 1516 RTI. (VR-Link and the MAK RTI allow you to use HLA-1.3-style FED files with IEEE-1516-based federates, and vice versa).

The main reason that consistency in FOM format is necessary is that IEEE 1516 uses different names for the "Root" classes of the Object class hierarchies. A 1.3-style FED file requires a Root class a 1516-style XML files requires a Root class called

HLAObjectRoot. The reason this can be a problem is that if the Logger is playing an HLA-1.3-based Logger file into a federation that is using a 1516-based XML file it might come across an instance of a class called, for example, "Object-Root.Vehicle". If it tries to register an object of this class, the RTI will complain that no such class exists. There might be a class called HLAObjectRoot.Vehicle in the current FOM, but the RTI or Logger does not know that this is actually the same class.