



MÄK RTI 3.4.1 Release Notes

This document provides the following release-specific information for MÄK RTI 3.4.1:

Supported Systems	2
Using Libraries and Binaries Built with Visual Studio 2005 and Later	2
Compiler Compatibility on Windows	3
FLEXlm Support	3
Third Party Library Dependencies	4
Patch Required for AMD Dual-processor Windows PCs	4
Backwards Compatibility	4
Network Compatibility	5
Compatibility with Other RTIs	5
New Features and Updates	6
Bug Fixes	6
Known Problems	7

MÄK RTI 3.0 has been verified by DMSO as fully compliant with the IEEE 1516 version of the HLA Interface Specification (SISO DLC HLA API 1516 (SISO-STD-004.1-2004).)

Copyright © 2010 VT MÄK, 68 Moulton St., Cambridge, MA 02138 All rights reserved.
MÄK Technologies®, VR-Forces®, B-HAVE®, RTIs Spy®, and VR-Link® are registered trademarks of VT MÄK. Document ID: RTI-3.4.1-2-100426

Supported Systems

Table 1 lists the platforms supported by the standard version of MÄK RTI 3.4.1. Please contact MÄK if you need it for another platform. Application code must be built with the indicated compilers in order to link to the MÄK RTI libraries.

Table 1: MÄK RTI: Platforms supported

Operating System	Compiler
Red Hat Enterprise Linux Workstation 4	Default compiler.
Red Hat Enterprise Linux Workstation 5. (32 bit and 64 bit libraries)	Default compiler.
Red Hat Fedora 7	Default compiler.
Windows XP	Microsoft Visual C++ 7.1, 8.0, 9.0**
Windows Vista*	Microsoft Visual C++ 8.0, 9.0**
*You must have administrator privileges to install VT MÄK products on Windows Vista.	
**The MSVC++ 9.0 version has 32 bit and 64 bit libraries.	

The RTI LS supports federates that run on the Solaris operating system. This version of the MÄK RTI only includes the LRC libraries. It does not include the rtiexec, RTIspy, or RTI Forwarder. You can link to the libraries if you are creating new federates on Solaris.

If you need to run an rtiexec, you must do so on Windows or Linux.

Table 2: RTI LS: Platforms supported

Operating System	Compiler
Sun Sparc Solaris 10	Sun C++ 5.8

Using Libraries and Binaries Built with Visual Studio 2005 and Later

All MÄK products built with Microsoft Visual Studio require the C Runtime Library to function. The C runtime libraries have always been available from Microsoft for download, they are also installed on a user's machine when a Microsoft compiler is installed. The C runtime libraries are not part of the normal Windows installation. For customers who plan to use MÄK products on machines that do not have a compiler installed, MÄK has historically distributed a copy of the C Runtime Libraries with MÄK products. These libraries were put in the *bin* directory used by the MÄK products. MÄK products would then use the libraries in the *bin* directory and customers would not have a problem if copies of the libraries were not already installed.

Unfortunately, with the release of the new C Runtime Libraries required by Microsoft Visual Studio 2005 (MSVC++8.0) and later, the libraries can no longer just be copied into the *bin* directory of an application. The libraries need to be installed correctly into Windows system folders. (The process is actually a little more complicated, a manifest file needs to be created to tell Windows where to find the libraries.)

To accommodate this change, MÄK is distributing the Windows installer for the C runtime libraries with all MÄK products released for MSVC++8.0 and later. The 32-bit installer is named *vcredist_x86.exe*; the 64-bit installer (if supported) is named *vcredist_x64.exe*. They are in the base directory of any installed MÄK product that requires them.

Running the installer requires Administrator privileges for the machine the installer is run on. MÄK has chosen to not integrate the MÄK installer and the Microsoft installer so as not to require users to have Administrator privileges to install MÄK products. Therefore, if you who do not have a compiler installed, or get error messages like “Software has not been installed correctly, please re-install”, you must apply the patch.

For more information see this Microsoft URL:

<http://msdn2.microsoft.com/en-us/library/ms235299.aspx>



You must ensure that the preprocessor defines `_SECURE_SCL=0`, and `_HAS_ITERATOR_DEBUGGING=0` are set for MSVC++8.0 and MSVC++9.0 builds. If these are not set, random crashes and assertions may be encountered during runtime.

Compiler Compatibility on Windows

MÄK provides versions of product releases that have been compiled with Microsoft Visual C++ 7.1, 8.0, and 9.0. When you run MÄK products together, for example, the Logger and a VR-Vantage application, we strongly recommend that you run versions compiled with the same compiler. Mixing products compiled with different versions of the compiler can result in program instability.

FLEXlm Support

MÄK RTI 3.4.1 uses FLEXlm 11.8 for all versions except the Windows VC++ 7.1 version, which continues to use FLEXlm 11.6. If you are upgrading from a version of the MÄK RTI that used an older version of FLEXlm, you must replace the files in the license server's FLEXlm directory with the files provided with this release. You do not need a new license. Licenses are forward compatible.

Third Party Library Dependencies

In addition to the Qt dependencies mentioned previously, the MÄK RTI 3.4.1 has the following dependencies:

- QT - 4.5 - <http://qt.nokia.com/>
- ZLIB - 1.2.3 - <http://www.zlib.net/>
- ICONV - 1.8 - <http://www.gnu.org/software/libiconv/>
- LIBXML2 - 2.6.22 - <http://www.xmlsoft.org/>

Patch Required for AMD Dual-processor Windows PCs

VR-Link-based products use a high resolution counter for time calculations on Windows PCs. Customers who are running Windows on PCs with multiple AMD Athlon 64-bit processors may notice clock jitter, which may cause time in MÄK products to run backwards. This occurs when the Windows scheduler changes the CPU the MÄK process is using. If the high resolution counters on each processor are not synchronized, the application may witness a decrease in the high resolution counter value stored in the processor causing an incorrect time calculation. To fix this problem customers, apply the AMD Dual-Core Optimizer patch provided by AMD. You can get the patch at:

http://www.amd.com/us-en/Processors/TechnicalResources/0,,30_182_871_9706,00.html



If you get an error when you try to access this URL, reload the page.

Backwards Compatibility

The MÄK RTI 3.4.1 libraries are not run-time compatible with previous versions. (In other words, you cannot have a federation execution in which some federates use MÄK RTI 3.4.1 and some use a previous version of the MÄK RTI.) However, the MÄK RTI 3.4.1 is link compatible with previous versions, so a federate does not need to be recompiled to use this version. We recommend that all federates use the same version of the RTI when operating within the same federation (or using the same *rtiexec*).

Network Compatibility

The MÄK RTI is not network compatible with other RTIs. (In general, no two RTI implementations are network compatible, due to differences in the low-level network mechanisms that they use.) Applications that want to interoperate in the same federation execution must all use the same RTI implementation. A federation can easily switch from one RTI implementation to another between runs, but during each run, all participants must agree on which RTI to use, much as they must also agree on which FOM to use.

Compatibility with Other RTIs

The MÄK RTI 1.3 implements the API dictated by the 1.3 version of the HLA Interface Specification, as amended by DMSO's official HLA 1.3 Interpretations document. All RTIs that are verified as compliant with the HLA 1.3 specification are written to this exact API standard. This insures that the MÄK RTI is link-compatible with other RTIs that have been verified as HLA compliant.

The MÄK RTI 1516 implements the SISO DLC HLA API¹ 1516 (SISO-STD-004.1-2004). This API supports dynamic link compatibility, which was problematic with the original IEEE 1516 API. The IEEE 1516 API only supports compile time compatibility (uses C++ templates and implementation-specific header files). The MÄK RTI is compatible with any RTI written to the SISO DLC HLA API 1516.

Because an RTI is typically accessed by an application through a dynamic library (*.dll* on Windows, *.so* on UNIX), applications do not need to be recompiled or relinked to switch among dynamic-link-compatible RTI implementations that have been built using the same compilers. The only requirement is that the appropriate version of the library be located within the shared library search path. For more information, please see Section 3.2, “[Compiling and Linking with the MÄK RTI 1.3](#)” in *MÄK RTI Reference Manual*.

i

Because the DMSO RTI NG v6 was last built with the MSVC++ 6.0 compiler, it is not link compatible with the MÄK RTI 3.4.1. However, updated versions of the DMSO RTI provided by other vendors using compilers supported by MÄK RTI 3.4.1 would be link compatible.

-
1. Simulation Interoperability Standards Organization Dynamic Link Compatible High Level Architecture Application Program Interface

New Features and Updates

MÄK RTI 3.4.1 is a maintenance release. It does not have any new product features. It has been issued to support the 64 bit Red Hat Enterprise Linux Workstation 5. To use MÄK RTI 3.4.1, you must upgrade your license server to FLEXlm 11.8 (except Windows VC++ 7.1). To do this, copy the files from *makRti3.4.1/flexlm11.8* to the flexlm directory on your license server.

Bug Fixes

The following bugs have been fixed in this release:

- The RTI sometimes crashed when using DDM when unsubscribing from a region while also being subscribed to the same attributes without a region.
- Improved performance for large federations using DDM.
- When using DDM, sometimes objects in some publication regions were not discovered when the subscription region changed.
- RTI 1516 crashed on exit when using DDM.
- MOM service reporting was not working for the attributeOwnershipDivestitureIfWanted and decodeDimensionHandle services.
- Specifying very small values for tick minimum did not work properly.
- Late joining federates that use the RTIspy web service sometimes crashed.
- A crash would occur after connecting to the rtiexec when `RTI_enableNetworkTesting` was set to 0.
- The RTI Forwarder was not printing all of the correct RID parameters when `RTI_dumpRid` was set to 1.
- Smart forwarding was being forcibly disabled when starting an rtiexec and using the RTI Assistant to choose connection information.
- The `RTI_disableUnlicensedForTwo` RID parameter had no effect.
- The help system did not work on Linux.
- There were GUI geometry issues on Linux.
- The RTI Assistant would hang after starting a federate if there was a trailing semi-colon at the end of the value for the `MAKLMGRD_LICENSE_FILE` environment variable.

Known Problems

This release has the following known problems:

- ♦ Distributed forwarder multicast subscription does not work for late-joining forwarders. With the introduction of the unified Distributed Forwarder a need arose to communicate between federates on a LAN and forwarders on remote LANs when a DM or DDM multicast group is joined or dropped, such that the forwarders can monitor or drop those groups on its LAN and forward messages back to the federates joined to such multicast groups. However the scheme to accomplish this does not work if the forwarder is not connected to the forwarder network when the federate joins the multicast group. The workaround is to ensure that the forwarder network is completely established prior to launching federates, or at the least, prior to allowing federates to attempt to join DM or DDM multicast groups.
- ♦ The MÄK Technologies Lisp (MTL) files used by MÄK products to specify configuration settings are parsed at startup by the RTI. When a configuration file has certain errors, such as unmatched parentheses, the parser will not necessarily return an error code. This can cause the RTI to reach a partially initialized state or cause the RTI to initialize itself with default RID values, causing unexpected behavior. This applies to lisp expressions in the RID file as well as the expressions passed to the 1516 createRTIambassador function.
- ♦ A workaround has been added to deal with situations where a host running the RTI Forwarder application has multiple network interface adapters (NICs) or has multiple IP addresses assigned to an interface, which may be the case if the RTI Forwarder host is connected to the WAN via a VPN tunnel. Under these circumstances the RTI Forwarder may fail to initiate connections to other forwarders if the IP address corresponding to its host in the Forwarder List section of the *routes.mtl* file does not match the IP address the RTI Forwarder application receives when it queries the host itself for its IP address. To correct this the IP addresses of the interfaces on which it will connect to other RTI Forwarders must be entered into the *routes.mtl* file Interface Address List section. At a minimum one such entry should correspond to the entry identifying the host in the Forwarder List section of the *routes.mtl* file. Please refer to Section 11.6, “[Configuring RTI Forwarders for Distributed Forwarding](#)” in *MÄK RTI Reference Manual* for details about the Interface Address List entry format.
- ♦ The HLA 1.3 version of the RTI can sometimes fail to throw an “ObjectAlreadyRegistered” exception if a federate tries to register an object with a name that is already being used by another object. The federate can register an object using a name that belongs to another object that is unknown to the local RTI component (LRC). The LRC only maintains the names of objects that are registered or discovered by the federate. While we plan to fix this problem, a good preventive measure is to always subscribe and tick the RTI before registering objects.

- ♦ The RTIsy browser-based GUI does not work well with Internet Explorer 6 or 7. While you will be able to see and use the RTIsy GUI with IE7, the page layout may be problematic, and some information may not be displayed correctly. For optimal use, MÄK recommends using Firefox (2.0 or later).